



Circular Shaker TRCS-602

www.chinascientific.com | info@chinascientific.com

Description

Circular Shaker TRCS-602 has an operational model that is continuous or counted down. It is available with a variety of brackets and fixtures, with a speed range of 100 to 500 rpm. It is equipped with a dual LCD screen, intended to display time and speed separately. It is provided with the mechanism of a DC brush motor system. It can bear a maximum load of weight. Have a 10mm orbital diameter.

Features:

It can bear a maximum load of weight

It is equipped with a dual LCD screen, intended to display time and speed separately

It is available with a variety of brackets and fixtures

It is provided with the mechanism of a DC brush motor system

Specifications :

Ambient Temperature	5 to 40 ?C
Amplitude	10 mm
Data Access	RS232
Dimensions (L x W x H)	425×355×90 mm
Humidity	0.8
Maximum Load	7.5 kg
Motor Type	DC motor
Power	20 W
Speed Display	LCD
Speed Range	100 to 500 rpm
Time setting range	0 to 19 h 59 min
Timing Display	LCD
Voltage	100 to240V, 50/60Hz
Weight	13.5 kg

www.chinascientific.com

W Parkway St Denton TX 76201, USA
Email: info@chinascientific.com | Website: www.chinascientific.com