



Horizontal Laminar flow cabinet TRHL-603

www.chinascientific.com | info@chinascientific.com

Description

Horizontal Laminar flow cabinet TRHL-603 is a local purification unit used in a dust-free and aseptic clean environment. A similar enclosure creates a particle-free working environment by passing air through a filtration system. It comes with an easy-to-use quasi-glass damper. Comes with a stainless steel working area, the Specification of the ultraviolet lamp is 1/10 W. It provides in a small and exquisite manner. It is presented with the air supply mode and supplies through both horizontal and vertical manner.

Features:

Cold-rolled plate welding equipped throughout the equipment

Comes with a stainless steel working area

It is presented with a HEPA filter

Built with a glass sliding door, and with a UV lamp and fluorescent lamp

The surface electrostatically sprayed

The air supply mode into the vertical and horizontal air supply

Controlled by a simple to use quasi-closed glass damper

It is small and exquisite

It can operate freely on the general workbench, making it ideal for use in small studios

A remote switch with fast controls the fan system

Specifications :

Average Wind Speed	0.25 to 0.45 m/s (Fast and slow)
Cleanliness Level	Class 100 @ $\pm 0.5\mu\text{M}$
High-Efficiency Filter Specification And Quantity	470×455×38×1
Illuminance	2300 Lx
Noise	262dB (A)
Number Of Colonies	20.5pcs/dish hour (290mm culture plate)
Overall Dimension	650×530×850 mm
Power Supply	AC single-phase 220V/50 Hz
Specification And Quantity Of Fluorescent Lamp/Ultraviolet Lamp	5W×1/10W×1
Vibration Half Peak	20.5 μM (x, y, z-direction)
Working Area	490×350×490 mm

www.chinascientific.com

W Parkway St Denton TX 76201, USA

Email: info@chinascientific.com | Website: www.chinascientific.com