

[www.chinascientific.com](http://www.chinascientific.com)



## Micro-spectrophotometer TRMS-603

[www.chinascientific.com](http://www.chinascientific.com) | [info@chinascientific.com](mailto:info@chinascientific.com)

## Description

Micro-spectrophotometer TRMS-603 is an innovative type of full-wavelength spectrophotometer for the detection of samples. The wavelength of the cuvette is 200nm to 850nm. Equipped with stainless steel and quartz fibre with Bluetooth and WIFI united in, allowing for remote control and printing of results. Built-in fibre to prevent fibre splitting as a response to external force collisions, which would cause irregular measurement results.

## Features:

There is no need to warm up checking can begin at any time

Built-in Win10 system, constructed 7-inch high-definition showcase, full touch operation

32GB of storage space is pre-installed

Two USB ports can be connected to a variety of devices

The platform is constructed out of stainless steel and quartz fibre

Built-in fibre to prevent fibre breakage caused by external force collision, resulting in chaotic measurement results

Built-in Bluetooth and WIFI allow for remote operation and wireless printing of results

Users can save measuring device result data and design techniques straight in spreadsheet mode with a digital manual

## Specifications :

<b>Absorbance Accuracy</b>	2 nm (FWHM Hg 546n m)
<b>Absorbance Range</b>	0.002 Abs
<b>Cuvette darkroom</b>	standard cuvette darkroom
<b>Cuvette minimum Volume</b>	50 $\mu$ l
<b>Cuvette wavelength Range</b>	200 nm to 850 nm
<b>Detection Time</b>	0.4 to 15000 ng/ $\mu$ l (ds-DNA)
<b>Detector</b>	3.5 kg
<b>Light Source</b>	20 $\times$ 30 $\times$ 20 cm
<b>Machine Size</b>	0.01 to 400 mg/ml (BSA)
<b>Nucleic acid Range</b>	1% (0.76 absorbance at 350nm)
<b>Optical Path</b>	1/0.5/0.05 mm automatic conversion
<b>Optical Range</b>	190 to 1100 nm
<b>Protein Range</b>	0.002 to 300 Abs (equivalent to 10mm optical path)
<b>Sample level Height</b>	5 mm
<b>Sample Volume</b>	0.3 to 2.0 $\mu$ l
<b>Trial cuvette Specifications (light path)</b>	1/2/5/10 mm
<b>Type</b>	Recyclable micro cuvette
<b>Wavelength Accuracy</b>	$\pm$ 1 nm
<b>Wavelength Resolution</b>	2 nm (FWHM Hg 546n m)
<b>Wavelength scanning Range</b>	190 to 850 nm
<b>Weight</b>	less than 3s

[www.chinascientific.com](http://www.chinascientific.com)

W Parkway St Denton TX 76201, USA  
Email: [info@chinascientific.com](mailto:info@chinascientific.com) | Website: [www.chinascientific.com](http://www.chinascientific.com)