



Vertical and Horizontal Laminar Flow Cabinet TRVHC-601

Description

Vertical and Horizontal Laminar Flow Cabinet TRVHC-601 material is stainless steel, and a wind volume adjustable fan system is used. Based on a one-dimensional system. It has a sliding glass door that allows for easy observation. The device prevents outside gas from entering the operating room, preventing a strange odor from entering. The range of illumination is 300LX.

Features:

The vertical closed bench effectively prevents outside gas from entering

Able to operate area and prevents the slightly odd aroma

A wind volume adjustable fan system

A light-touch type switch and a dual-speed voltage regulation device

the personalized design takes into account all of the user's requirements

It uses a spring-type sliding door to allow the door to be geared in the desired position

It is easier to use

Filters and electric components can easily be exchanged by opening the front cover directly

Use the LED panel to your advantage

The stainless steel used for the workspace

Specifications :

Dimension Of Working Area(W1×D1×H1)	870×500×620mm
Efficient Filter Specifications And Quantities	865×600×38×1/865×484×38×1
Half Ventilation Peak Value	? 3?m(XYZ direction)
Illumination	?300LX
MaximumPower Consumption	300W
Noise	?62dB
Number of Bacteria	?0.5per utensil. Hour(90mm utensil)
Overall Dimension W×D×H	1050×760×1800mm
Power Supply	AC, 220 V/50Hz
Specification And Number Of Fluorescent Lamp Or UV Lamp Of Ultraviolet Lights	20W×1/20W×1
Suited Number	Single-Single
The Average Wind Speed	0.25 to 0.45m/s(Speed two-speed)
Weight	150 Kg

www.chinascientific.com

W Parkway St Denton TX 76201, USA

Email: info@chinascientific.com | Website: www.chinascientific.com